

**Feed ejectors - rotatable**  
High suction power for handling with high leakage



**Product Description**

- > High suction power for safe handling of air-permeable products or generally in the presence of high leakage
- > Gentle transportation of powdery substances or small-size products such as granular material, coffee, flour
- > Extraction of non-aggressive vapors and gases
- > The volume of suction air and required vacuum level can be adjusted to match the level of compressed air by turning the suction pipe, allowing for an energy-efficient increase in performance without increasing air consumption
- > Can even be used in rough conditions thanks to the robust, maintenance-free construction without moving parts
- > Stainless steel designs for great cleaning when transporting foods and for abrasive media
- > Extremely flexible integration into gripper systems thanks to any mounting position

**Technical data**

Item no.	Nozzle diameter [mm]	Pressure range [bar]	Optimal feed pressure [bar]	Final vacuum [mbar]	Suction power [NI/min]	Air consumption [NI/min]	Operating temperature [°C]	Weight [g]	Material	Suitable silencers
65.701	7	4 - 7	5	0 - 850	0 - 284	0 - 235	-20 - 80	105	Aluminium anodised	72.029
65.711	10	4 - 7	5	0 - 850	0 - 848	0 - 481	-20 - 80	275	Aluminium anodised	72.031
65.731	20	4 - 7	5	0 - 850	0 - 3402	0 - 1246	-20 - 80	550	Aluminium anodised	72.033
65.701-S	7	4 - 7	5	0 - 850	0 - 284	0 - 235	-20 - 80	300	Stainless steel	72.029
65.711-S	10	4 - 7	5	0 - 850	0 - 848	0 - 481	-20 - 80	700	Stainless steel	72.031
65.731-S	20	4 - 7	5	0 - 850	0 - 3402	0 - 1246	-20 - 80	1500	Stainless steel	72.033

**Functional principle**

