



SERIE 108 RTC



RTC COUPLINGS

QUICK COUPLINGS FOR HYDRAULIC
COUPLINGS FOR HYDRAULIC INOX

ENCHUFE SERIE 108 RTC



6
6
9
12
16

108.06 SFB 13
108.06 SFB 17
108.09 SFB 17
108.12 SFB 21
108.16 SFB 26



6
6
9
12
16

108.06 PFB 13
108.06 PFB 17
108.09 PFB 17
108.12 PFB 21
108.16 PFB 26

PRESIÓN TRABAJO

rtc 108.06 180 bar (2610 PSI)
rtc 108.07 180 bar (2610 PSI)
rtc 108.09 180 bar (2610 PSI)
rtc 108.12 180 bar (2610 PSI)
rtc 108.16 180 bar (2610 PSI)



info@hidrafluid.es
Telf: (+34) 976 24 32 10

www.rtc-tec.com
QUICK CONNECT TECHNOLOGY



SERIE 108 RTC



RTC COUPLINGS

QUICK COUPLINGS FOR HYDRAULIC
COUPLINGS FOR HYDRAULIC INOX

ENCHUFE SERIE 108 RTC

	6	108.06 DGB 13	108.06 SFB 13
	6	108.06 DGB 17	108.06 SFB 17
	9	108.09 DGB 17	108.09 SFB 17
	12	108.12 DGB 21	108.12 SFB 21
	16	108.16 DGB 26	108.16 SFB 26

	6	108.06 DUB 13	108.06 PFB 13
	6	108.06 DUB 17	108.06 PFB 17
	9	108.09 DUB 17	108.09 PFB 17
	12	108.12 DUB 21	108.12 PFB 21
	16	108.16 DUB 26	108.16 PFB 26

ACERO INOXIDABLE

VITON: -20 °C - 200 °C

FFKM: -10 °C - 280 °C

PRESIÓN TRABAJO: 0-180 BAR

DOBLE CIERRE. DISPONIBLE FORMATO PUSH PULL



info@hidrafluid.es
Telf: (+34) 976 24 32 10

www.rtc-tec.com
QUICK CONNECT TECHNOLOGY