



SERIE 105 RTC



RTC COUPLINGS

QUICK COUPLINGS FOR TEMPERATURE REGULATION
QUICK COUPLINGS FOR LUBRICATION

	9		105.09 SFB 17
	12		105.12 SFB 21
	16		105.16 SFB 26
	20		105.20 SFB 26
	20		105.20 SFB 33
	25		105.25 SFB 33
	25		105.25 SFB 42

	9		105.09 SMB 17
	12		105.12 SMB 21
	16		105.16 SMB 26
	20		105.20 SMB 33
	25		105.25 SMB 42

PRESIÓN TRABAJO

rtc 105.09 16 bar (232 PSI)

rtc 105.12 16 bar (232 PSI)

rtc 105.16 16 bar (232 PSI)

rtc 105.20 16 bar (232 PSI)

rtc 105.25 16 bar (232 PSI)



SERIE 105 RTC



RTC COUPLINGS

QUICK COUPLINGS FOR TEMPERATURE REGULATION
QUICK COUPLINGS FOR LUBRICATION

	9		105.09 PFB 17
	12		105.12 PFB 21
	16		105.16 PFB 26
	20		105.20 PFB 26
	20		105.20 PFB 33
	25		105.25 PFB 33
	25		105.25 PFB 42

	9		105.09 PMB 17
	12		105.12 PMB 21
	16		105.16 PMB 26
	20		105.20 PMB 33
	25		105.25 PMB 42