

2-jaw self-centering angular pneumatic gripper series AA-25-NO

- Single-acting.
- Spring opening.
- Closing stroke adjustment.
- Optional magnetic sensors.



	AA-25-NO
Fluido <i>Medium</i>	Aria compressa filtrata, lubrificata / non lubrificata <i>Filtered, lubricated / non lubricated compressed air</i>
Pressione di esercizio <i>Operating pressure range</i>	2.5 ÷ 8 bar
Temperatura di esercizio <i>Operating temperature range</i>	5 ÷ 60 °C.
Corsa <i>Stroke</i> (±1°)	2 x 14°
Coppia di chiusura per griffa a 6 bar <i>Closing torque at 6 bar on each jaw</i>	125 Ncm
Coppia di chiusura totale a 6 bar <i>Total closing torque at 6 bar</i>	250 Ncm
Coppia di apertura per griffa a 0 bar <i>Opening torque at 0 bar on each jaw</i>	25 Ncm
Coppia di apertura totale a 0 bar <i>Total opening torque at 0 bar</i>	50 Ncm
Frequenza max funzionamento continuativo <i>Maximum working frequency</i>	2 Hz
Consumo d'aria per ciclo <i>Cycle air consumption</i>	2 cm ³
Tempo di chiusura senza carico <i>Closing time without load</i>	0.02 s
Peso <i>Weight</i>	105 g