

Feed ejectors - with a large passage

Very high suction power for high transportation throughput



Product Description

- > Very high suction power for high transportation throughput
- > Gentle transportation of powdery substances or small-size products such as granular material, pills, coffee, flour, chippings
- > Extraction of non-aggressive vapors and gases
- > Can even be used in rough conditions thanks to the robust, maintenance-free construction without moving parts
- > Extremely flexible integration into gripper systems thanks to any mounting position

Ordering notes

- > Mounting options:
65.752: Connections for vacuum and outlet on both sides using G3/8 female thread (see drawing)

Technical data

Item no.	Nozzle diameter [mm]	Pressure range [bar]	Max. feed pressure [bar]	Final vacuum [mbar]	Suction power at 5,5 bar [NL/min]	Air consumption at 2,8 bar [NL/min]	Air consumption at 5,5 bar [NL/min]	Operating temperature [°C]	Weight [g]	Suitable silencers
65.742	7	2.5 - 6	7	260	295	85	160	-10 - 80	92	-
65.752	10	2.5 - 6	7	160	425	95	170	-10 - 80	81	72.030
65.762	13	2.5 - 6	7	350	870	395	680	-10 - 80	177	-
65.772	19	2.5 - 6	7	280	1825	790	1365	-10 - 80	380	-
65.792	38	2.5 - 6	7	90	4400	405	695	-10 - 80	607	-
65.802	38	2.5 - 6	7	90	5610	790	1356	-10 - 80	777	-

Functional principle

