

rtc TYPE 200




Flow size

rtc 200.04	4 mm
rtc 200.06	6 mm
rtc 200.07	7 mm
rtc 200.09	9 mm
rtc 200.12	12 mm
rtc 200.19	19 mm
rtc 200.32	32 mm
rtc 200.50	50 mm

Compatible: Walther LP Type

Temperature Range
 -20°C +100°C (-4°F +212°F) Nitril (N)
 -10°C +180°C (+14°F +356°F) FPM (V)

Working Pressure
 30 - 100 bar (435 - 1450 PSI)



rtc TYPE 201



Flow size

rtc 201.06	6 mm
rtc 201.07	7 mm
rtc 201.12	12 mm
rtc 201.19	19 mm
rtc 201.25	25 mm
rtc 201.32	32 mm
rtc 201.50	50 mm

Compatible: Walther MD Type

Temperature Range
 -20°C +100°C (-4°F +212°F) Nitril (N)
 -10°C +180°C (+14°F +356°F) FPM (V)

Working Pressure
 100 - 250 bar (1450 - 3625 PSI)



rtc TYPE 202



Flow size

rtc 201.04	4 mm
rtc 201.06	6 mm
rtc 201.10	10 mm
rtc 201.16	16 mm
rtc 201.20	20 mm
rtc 201.32	32 mm
rtc 201.50	50 mm

Compatible: Walther HP Type

Temperature Range
 -20°C +100°C (-4°F +212°F) Nitril (N)
 -10°C +180°C (+14°F +356°F) FPM (V)

Working Pressure
 200 - 2000 bar (2900 - 29000 PSI)



rtc TYPE 203



Flow size

rtc 203.09	9 mm
rtc 203.12	12 mm
rtc 203.19	19 mm
rtc 203.32	32 mm
rtc 203.50	50 mm

Compatible: Walther TE Type

Temperature Range
 -20°C +270°C (-4°F +518°F) PTFE (T)

Working Pressure
 30 - 100 bar (435 - 1450 PSI)

